



## 4MP IP DOME CAMERA

- 1/2.8" HD-CMOS
- IR Dome Camera
- 4.0MP Resolution @ (2560x1440)P
- 2.8mm HD Lens
- 2-Array LED's / up to 20-30Mtr.
- Mic Inbuilt & PoE Supported
- H.264/H.265/H.265+ Supported



## SPECIFICATION

MODEL	FE-IP-40ID-AR2-A
Image sensor	1/2.8" HD-CMOS
Video compression	HH.264/.265/H.265+ Video compression. Support dual stream
Minimum illumination	0.5 Lux; 0Lux with IR on
Shutter type	Auto/Manual, 1/3(4) ~ 1/10,000s
Frame rate	4.0MP@19fps
White balance	Auto
P2P	Supported
Lens mount	2.8mm MP HD Lens
Image output	Main stream: 2560x1440@1-19fps / Sub stream: 640x360@1-19fps
ONVIF	Yes
Network interface	1RJ45 Ethernet interface
IR Led / IR distance	2-Array LED's / up to 20-30Mtr..
Network function	Free client software
Power supply	12VDC / 2A
Current drawn	500mA (Max.)
Working condition	-10°C to +55°C (32°F-133°F) , 10% - 90%PH

\*Product casing and specifications are subject to change without prior notice..