

1-8 PORT 250M DISTANCE POE

- 8*10/100Mbps PoE Ports, 2*10/100Mbps Uplink Ports
- Support IEEE802.3af/at
- Support Restrained Network Storm.
- Max Transmission Distance upto 250m with PoE Power
- Built-in Power Supply
- Maximum Power of Single PoE Port: 30W
- Maximum PoE Power: 120W
- Adopts Store-And-Forward Architecture
- Fanless, Natural Cooling, Small, Compact Design
- Support Lightning Protection 2KV



SPECIFICATION

MODEL	FE-POE-82N
Power Adapter Voltage	AC 110V-240V
Consumption	120W(52V 2.3A)
PoE Ethernet Port	1-8 port:10/100Mbps
Ethernet Port	Uplink port:10/100Mbps
Transmission Distance	100Mbps:0-100m / 10Mbps:0-250m / Uplink Port:0-100m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.3ab
Switching Capacity	2Gbps
Packet Buffer Memory	1Mbits
Throughput	1.488Mbps
MAC Table	1K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:1488000pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	1/2 +,3/6 -,8 core power supply
PoE Power	af=15.4w,at=30w for each port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT 100Mbps: PoE Status Indicator, Power Indicator, Extender
Working temperature	0°C~55°C
Relative Humidity	20-95%
Storage temperature	-20°C~70°C
Dimension(L*W*H)	220mm*140mm*45mm
Color & Weight	Black 1.05Kg

*Product casing and specifications are subject to change without prior notice..

