


Dual Light Color Camera PROJECT SERIES DOME & BULLET CAMERA



- HIGH DEFINITION**
High Definition Image Sensor
- HI-FIDELITY**
InBuilt Mic
- SMART H.265+**
Ultra Low Bit Rate Codec
- WEATHERPROOF**
Metal Body Construction
- DUAL LIGHT**
IR & Color LED's
- 2-WAY AUDIO**




4G & WIFI MINI PTZ CAMERA



GOFFLASH INTERNATIONAL

As a continuing policy of product development at NETPRO, the design and specifications are subject to change. They may vary from model to model. Colour/shades may vary due to printing restrictions.

For Demo kindly visit Us!
SOUTH DELHI, DELHI-110044, INDIA
 info@goflashinternational.com | www.goflashinternational.com
<https://www.facebook.com/GoFlashInternational/>
 For Support : +91-7827518810 / 7011769595



For internal consumption only. Not for public distribution or information on any product*.

Product catalogue



MadeByBharat
By Indians, For Indians

www.goflashinternational.com | info@goflashinternational.com



IP COLOR CAMERA

IP SERIES - 4MP H.265+

DOME PLASTIC CAM

- CMOS Sensor
- H.265/H.265+ Support
- 3.6mm HD Lens
- PoE & ONVIF Support
- 4MP@2560x1440IP
- Distance upto 20-30Mtr.
- Frame Rate 4MP@19fps
- Color Video Recording
- Audio Recording

BULLET PLASTIC CAM

- CMOS Sensor
- H.265/H.265+ Support
- 3.6mm HD Lens
- PoE & ONVIF Support
- 4MP@2560x1440IP
- Distance upto 20-30Mtr.
- Frame Rate 4MP@19fps
- Color Video Recording
- Audio Recording

BULLET METAL CAM

- CMOS Sensor
- H.265/H.265+ Support
- 3.6mm HD Lens
- PoE & ONVIF Support
- 4MP@2560x1440IP
- Distance upto 20-30Mtr.
- Frame Rate 4MP@19fps
- Color Video Recording
- Audio Recording

IP SERIES - 5MP H.265+

DOME PLASTIC CAM

- CMOS Sensor
- H.265/H.265+ Support
- 3.6mm HD Lens
- PoE & ONVIF Support
- 5MP@2560x1920IP
- Distance upto 20-30Mtr.
- Frame Rate 5MP@19fps
- Color Video Recording
- Audio Recording

BULLET PLASTIC CAM

- CMOS Sensor
- H.265/H.265+ Support
- 3.6mm HD Lens
- PoE & ONVIF Support
- 5MP@2560x1920IP
- Distance upto 20-30Mtr.
- Frame Rate 5MP@19fps
- Color Video Recording
- Audio Recording

BULLET METAL CAM

- CMOS Sensor
- H.265/H.265+ Support
- 3.6mm HD Lens
- PoE & ONVIF Support
- 5MP@2560x1920IP
- Distance upto 20-30Mtr.
- Frame Rate 5MP@19fps
- Color Video Recording
- Audio Recording

IP NORMAL CAMERA

IP SERIES - H.265+

4MP IP DOME

- Image CMOS Sensor
- IR Dome Camera
- 4.0MP @ (2560x1440)IP
- 3.6mm HD Lens
- 2-Array LED's
- IR Distance upto 20-30Mtr.
- PoE & Mic Supports
- H.264 / H.265 / H.265+

5MP IP DOME

- Image CMOS Sensor
- IR Dome Camera
- 5.0MP @ (2560x1920)IP
- 3.6mm HD Lens
- 2-Array LED's
- IR Distance upto 20-30Mtr.
- PoE & Mic Supports
- H.264 / H.265 / H.265+

4MP IP BULLET

- Image CMOS Sensor
- IR Dome Camera
- 4.0MP @ (2560x1440)IP
- 3.6mm HD Lens
- 2-Array LED's
- IR Distance upto 20-30Mtr.
- PoE & Mic Supports
- H.264 / H.265 / H.265+

NETWORK POE SWITCH

UPLINK POE SWITCH (10/100/1000)MBPS

4-PORT FE-POE-42N

- PoE Ethernet 4*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 1000Mbps
- Consumption: 120W(52V 1.44A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 1.2Gbps
- Throughput: 0.9Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 0.95Kg

SPEED 10/100MBPS

8-PORT FE-POE-82N

- PoE Ethernet 8*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 1000Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 2Gbps
- Throughput: 1.488Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 0.95Kg

SPEED 10/100MBPS

8-PORT FE-POE-8NGS

- PoE Ethernet 8*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 1000Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 5.6Gbps
- Throughput: 4.1664Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 1.05Kg

SPEED 10/100/1000MBPS

16-PORT FE-POE-1621GS

- PoE Ethernet 16*Port: 10/100Mbps
- Uplink & SFP 2*Port: 1000Mbps
- Consumption: 250W(52V 4.8A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 7.6Gbps
- Throughput: 5.6544Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 4.2Kg

SPEED 10/100/1000MBPS

24-PORT FE-POE-24N2G2S

- PoE Ethernet 24*Port: 10/100Mbps
- Uplink & SFP 2*Port: 1000Mbps
- Consumption: 300W(52V 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 12.8Gbps
- Throughput: 8.52224Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 5.2Kg

SPEED 10/100/1000MBPS

FULL GIGA POE SWITCH (1000)MBPS

4-PORT FE-POE-41FGS

- PoE Ethernet 4*Port: 1000Mbps
- Uplink & SFP Port 1+1: 1000Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 12Gbps
- Throughput: 8.928Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 1.05Kg

SPEED 1000MBPS

8-PORT FE-POE-8FGS

- PoE Ethernet 8*Port: 1000Mbps
- Uplink & SFP 2+2*Port: 1000Mbps
- Consumption: 150W(52V 2.88A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 20Gbps
- Throughput: 14.88Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 2.5Kg

SPEED 1000MBPS

FULL GIGA POE SWITCH (1000)MBPS

16-PORT FE-POE-162G1SF

- PoE Ethernet 16*Port: 1000Mbps
- Uplink & SFP 2+2*Port: 1000Mbps
- Consumption: 300W(52V 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 38Gbps
- Throughput: 29.41Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 4.2Kg

SPEED 1000MBPS

24-PORT FE-POE-24G2G2GSF

- PoE Ethernet 24*Port: 1000Mbps
- Uplink & SFP 2+2*Port: 1000Mbps
- Consumption: 300W(52V 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 56Gbps
- Throughput: 43.34Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 5.68Kg

SPEED 1000MBPS

IP COLOR CAMERA

AHD SERIES - 2.4MP

FE-AHD-24ID-AR2

- 1/2.9" HD-CMOS
- IR Dome Camera
- Full HD@1920x1080P (2.4MP)
- 3.6mm MP HD Lens
- 2-IR Array LED's
- IR Distance 20-30Mtr.

FE-AHD-24IB-AR4

- 1/2.9" HD-CMOS
- IR Bullet Camera
- Full HD@1920x1080P (2.4MP)
- 3.6mm MP HD Lens
- 4-IR Array LED's
- IR Distance 20-30Mtr.

FE-AHD-24IB18

- 1/2.9" HD-CMOS
- IR Bullet Camera
- Full HD@1920x1080P (2.4MP)
- 3.6mm MP HD Lens
- 18-IR LED's
- IR Distance 20-30Mtr.

AHD SERIES - 5MP

FE-AHD-51D-AR2

- 1/2.7" HD-CMOS
- IR Dome Camera
- Full HD@2560x1920P (5MP)
- 3.6mm MP HD Lens
- 2-IR Array LED's
- IR Distance 20-30Mtr.

FE-AHD-501B-AR4

- 1/2.7" HD-CMOS
- IR Bullet Camera
- Full HD@2560x1920P (5MP)
- 3.6mm MP HD Lens
- 4-IR Array LED's
- IR Distance 20-30Mtr.

FE-AHD-501B18

- 1/2.7" HD-CMOS
- IR Bullet Camera
- Full HD@2560x1920P (5MP)
- 3.6mm MP HD Lens
- 18-IR LED's
- IR Distance 20-30Mtr.

DIGITAL VIDEO RECORDER (DVR)

AHD SERIES - H.265

4/8 CHANNEL NVR

- Support 5MP Recording
- Video: 4/8Ch BNC, 1Ch VGA, 1Ch HDMI Output
- Playback: 4Ch Playback
- Audio: 1Ch RCA input, 1Ch RCA output
- Monitoring image quality: 5M-N(1296x1944)
- Upto 8TB SATA HDD*1
- IVA Video Analytics
- Line Crossing
- Object Detecon
- Support, Android, iPhone, Mac
- Dropbox Recording Supported.

16 CHANNEL NVR

- Support 5MP Recording
- Video: 16Ch BNC, 1Ch VGA, 1Ch HDMI Output
- Playback: 16Ch Playback
- Audio: 4Ch RCA input, 1Ch RCA output
- Monitoring image quality: 5M-N(1296x1944)
- Upto 8TB SATA HDD*2
- IVA Video Analytics
- Line Crossing
- Object Detecon
- Support, Android, iPhone, Mac
- Dropbox Recording Supported.

32 CHANNEL NVR

- Support 5MP Recording
- Video: 32Ch BNC, 1Ch VGA, 1Ch HDMI Output
- Playback: 16Ch Playback
- Audio: 16Ch RCA input, 1Ch RCA output
- Monitoring image quality: 5M-N(1296x1944)
- Upto 8TB SATA HDD*4
- IVA Video Analytics
- Line Crossing
- Object Detecon
- Support, Android, iPhone, Mac
- Dropbox Recording Supported.

IP PTZ CAMERA

IP SERIES - H.265+

3MP PTZ IP CAMERA

- 3MP HD CMOS Sensor
- H.265/H.265+ Support
- 36X Optical Zoom
- PoE & ONVIF Support
- 3MP@2048x1536IP
- IP 66 Weather Proof
- 360 Unlimited Rotation
- Frame Rate 3MP@25fps
- White Balance Auto
- P2P Support

4MP PTZ IP CAMERA

- 4MP HD CMOS Sensor
- H.265/H.265+ Support
- 36X Optical Zoom
- PoE & ONVIF Support
- 4MP@2688x1440IP
- IP 66 Weather Proof
- 360 Unlimited Rotation
- Frame Rate 4MP@19fps
- White Balance Auto
- P2P Support

5MP PTZ IP CAMERA

- 5MP HD CMOS Sensor
- H.265/H.265+ Support
- 36X Optical Zoom
- PoE & ONVIF Support
- 5MP@2560x1920IP
- IP 66 Weather Proof
- 360 Unlimited Rotation
- Frame Rate 5MP@19fps
- White Balance Auto
- P2P Support

NETWORK VIDEO RECORDER (NVR)

IP SERIES - H.265+

8 CHANNEL NVR

- Image sensor: H13798M
- Camera: Upto 8MP Supported.
- Video compression: 8Ch, 4K
- HDMI Output: HDMI: 1080P, 2K (2560x1440)
- Video: 8Ch Network Video Input
- Audio: 8Ch Network Audio Input
- Local playback: 1Ch
- Digital zoom: Yes
- Protocol: ONVIF
- Bandwidth: 80Mbps
- Mobile Phone: Android, iPhone, Mac
- HDD capacity: Upto 6TB SATA Interface HDD*1

16 CHANNEL NVR

- Image sensor: H13798M
- Camera: Upto 8MP Supported.
- Video compression: 16Ch, 4K
- HDMI Output: HDMI: 1080P, 2K (2560x1440)
- Video: 16Ch Network Video Input
- Audio: 16Ch Network Audio Input
- Local playback: 1Ch
- Digital zoom: Yes
- Protocol: ONVIF
- Bandwidth: 80Mbps
- Mobile Phone: Android, iPhone, Mac
- HDD capacity: Upto 6TB SATA Interface HDD*1

32 CHANNEL NVR

- Image sensor: H13798M
- Camera: Upto 8MP Supported.
- Video compression: 32Ch, 4K
- HDMI Output: HDMI: 1080P, 4K
- Video: 32Ch Network Video Input
- Audio: 32Ch Network Audio Input
- Local playback: 2Ch, 4K
- Digital zoom: Yes
- Protocol: ONVIF
- Bandwidth: 240Mbps
- Mobile Phone: Android, iPhone, Mac
- HDD capacity: Upto 6TB SATA Interface HDD*2/4

CCTV POWER SUPPLY (SMPS)

SWITCHING MODE POWER SUPPLY

FE-SMPS-4CH

- Input Voltage: AC 110-285V
- Input Frequency: 50Hz
- Illumination: 200 mA @230V
- Input Current: 200 mA @230V
- Output Voltage: DC 12V-DC 15V
- Output current: 4800 mA Max.

FE-SMPS-8CH

- Input Voltage: AC 110-285V
- Input Frequency: 50Hz
- Illumination: 200 mA @230V
- Input Current: 290 mA @230V
- Output Voltage: DC 12V-DC 15V
- Output current: 7200 mA Max.

FE-SMPS-16CH

- Input Voltage: AC 110-285V
- Input Frequency: 50Hz
- Illumination: 200 mA @230V
- Input Current: 590 mA @230V
- Output Voltage: DC 12V-DC 15V
- Output current: 9600 mA Max.

SWITCHING MODE POWER SUPPLY

FE-SMPS-4CH

- Input Voltage: AC 110-285V
- Input Frequency: 50Hz
- Illumination: 200 mA @230V
- Input Current: 200 mA @230V
- Output Voltage: DC 12V-DC 15V
- Output current: 4800 mA Max.

FE-SMPS-8CH

- Input Voltage: AC 110-285V
- Input Frequency: 50Hz
- Illumination: 200 mA @230V
- Input Current: 290 mA @230V
- Output Voltage: DC 12V-DC 15V
- Output current: 7200 mA Max.

FE-SMPS-16CH

- Input Voltage: AC 110-285V
- Input Frequency: 50Hz
- Illumination: 200 mA @230V
- Input Current: 590 mA @230V
- Output Voltage: DC 12V-DC 15V
- Output current: 9600 mA Max.

4G & WIFI DOME & BULLET CAMERA

3mp 4G Bullet Camera with Lan

- 4G connection; QR Code configuration
- Micro SD Card Support upto 256GB
- All time Color Camera
- Cloud storage (optional)
- Full Duplex Audio Intercom with Built-in high sensitivity speaker and mic
- Intelligent Human Detection, Area motion detection, Realtime Push Notification on Mobile App
- Customized Pre-recorded Audio Message Announcement for Audio Alerts
- "IPPRO, EseeCloud" Mobile app and PC client software for remote monitoring
- Alexa Support

3mp 4G Dome Camera

- 4G connection; QR Code configuration
- Micro SD Card Support upto 256GB
- All time Color Camera
- Cloud storage (optional)
- Full Duplex Audio Intercom with Built-in high sensitivity speaker and mic
- Intelligent Human Detection, Area motion detection, Realtime Push Notification on Mobile App
- Customized Pre-recorded Audio Message Announcement for Audio Alerts
- "IPPRO, EseeCloud" Mobile app and PC client software for remote monitoring
- Alexa Support

3mp WIFI (HA60P) Bullet Camera

- Wi-Fi connection; QR Code configuration
- All time Color Camera
- Micro SD Card Support upto 256GB
- Cloud storage (optional)
- Full Duplex Audio Intercom with Built-in high-sensitivity Mic and Speaker
- Intelligent Human Detection, Area motion detection, Realtime Push Notification on Mobile App
- Customized Pre-recorded Audio Message Announcement for Audio Alerts
- "IPPRO, EseeCloud" Mobile app and PC client software for remote monitoring
- Alexa Support

3mp Wifi (MY007A) Dome Camera

- Wi-Fi connection; QR Code configuration
- All time color Camera
- Intelligent Motion/Human based Tracking
- Micro SD Card support up to 256GB
- Cloud storage (optional)
- Full Duplex Audio Intercom with Built-in high-sensitivity Mic and Speaker
- Hotspot connection; can view and video playback without internet
- Intelligent Human Detection, Area motion detection, Realtime Push Notification on Mobile App
- Customized Pre-recorded Audio Message Announcement for Audio Alerts
- "IPPRO, EseeCloud" Mobile app and PC client software for remote monitoring
- Alexa Support